

Package: Rtinycc (via r-universe)

July 13, 2026

Title Builds the 'TinyCC' Command-Line Interface and Library for 'C' Scripting in 'R'

Version 0.1.11.9001

Description Builds the 'TinyCC' (Tiny 'C' Compiler) command-line interface and library for package use in 'R'. The package compiles 'TinyCC' from source and provides R functions to interact with the compiler. 'TinyCC' can be used for header preprocessing, just-in-time compilation of 'C' code in 'R', and lightweight 'C' scripting workflows.

License GPL (>= 3)

Copyright See inst/LICENSE.note for bundled TinyCC copyright and licensing details.

Depends R (>= 4.4.0)

Imports lambda.r

Suggests bench, callme, knitr, rmarkdown, tinytest, treesitter.c (>= 0.0.4)

VignetteBuilder knitr

SystemRequirements GNU make

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

URL <https://github.com/abiomix/abiomix-r-open>,
<https://github.com/sounkou-bioinfo/Rtinycc>,
<https://sounkou-bioinfo.github.io/Rtinycc/>

BugReports <https://github.com/abiomix/abiomix-r-open/issues>

Additional_repositories <https://abiomix.r-universe.dev>

Config/abiomix/public-license GPL-3.0-or-later

Config/abiomix/commercial-license Separate written agreement for Abiomix-owned contributions

Config/abiomix/license-policy <https://github.com/abiomix/abiomix-r-open/blob/main/LICENSES.md>

Config/pak/sysreqs make

Repository <https://abiomix.r-universe.dev>

Date/Publication 2026-07-13 08:37:42 UTC

RemoteUrl <https://github.com/abiomix/abiomix-r-open>

RemoteRef HEAD

RemoteSha dd82290ba296385fcc7d7dfed339886e9deb41a2

RemoteSubdir packages/Rtinycc

Contents

\$.tcc_compiled	4
as.character.tcc_cstring	5
blas_lapack_info	5
generate_trampoline	6
get_external_ptr_addr	6
is_callback_type	7
parse_callback_type	7
print.tcc_callback	8
print.tcc_compiled	8
print.tcc_cstring	9
print.tcc_ffi	9
tcc_add_file	10
tcc_add_include_path	10
tcc_add_library	11
tcc_add_library_path	11
tcc_add_symbol	12
tcc_add_sysinclude_path	12
tcc_bind	13
tcc_call_symbol	14
tcc_callback	15
tcc_callback_async_drain	16
tcc_callback_async_schedule	16
tcc_callback_close	17
tcc_callback_ptr	17
tcc_callback_valid	18
tcc_compile	18
tcc_compile_string	19
tcc_container_of	19
tcc_cstring	20
tcc_cstring_object	20
tcc_data_ptr	21
tcc_enum	21
tcc_ffi	22
tcc_field_addr	22

tcc_free	23
tcc_generate_bindings	24
tcc_get_symbol	25
tcc_global	25
tcc_header	26
tcc_include	27
tcc_include_paths	27
tcc_introspect	28
tcc_library	28
tcc_library_path	29
tcc_link	29
tcc_list_symbols	31
tcc_malloc	31
tcc_map_c_type_to_ffi	32
tcc_null_ptr	33
tcc_options	33
tcc_output	34
tcc_path	34
tcc_prefix	35
tcc_ptr_addr	35
tcc_ptr_free_set_null	36
tcc_ptr_is_null	36
tcc_ptr_is_owned	37
tcc_ptr_set	37
tcc_ptr_utils	38
tcc_read_bytes	38
tcc_read_cstring	39
tcc_read_f32	39
tcc_read_f64	40
tcc_read_i16	40
tcc_read_i32	41
tcc_read_i64	41
tcc_read_i8	42
tcc_read_ptr	42
tcc_read_u16	43
tcc_read_u32	43
tcc_read_u64	44
tcc_read_u8	44
tcc_recompile	45
tcc_relocate	45
tcc_run_cli	46
tcc_set_options	46
tcc_source	47
tcc_state	47
tcc_struct	48
tcc_struct_raw_access	48
tcc_symbol_is_valid	49
tcc_treesitter_bindings	49

tcc_treesitter_defines	50
tcc_treesitter_enum_bindings	51
tcc_treesitter_enum_members	52
tcc_treesitter_enums	52
tcc_treesitter_functions	53
tcc_treesitter_global_types	54
tcc_treesitter_globals	54
tcc_treesitter_struct_accessors	55
tcc_treesitter_struct_bindings	56
tcc_treesitter_struct_members	56
tcc_treesitter_structs	57
tcc_treesitter_union_accessors	58
tcc_treesitter_union_bindings	59
tcc_treesitter_union_members	59
tcc_treesitter_unions	60
tcc_union	61
tcc_write_bytes	61
tcc_write_f32	62
tcc_write_f64	62
tcc_write_i16	63
tcc_write_i32	63
tcc_write_i64	64
tcc_write_i8	64
tcc_write_ptr	65
tcc_write_u16	65
tcc_write_u32	66
tcc_write_u64	66
tcc_write_u8	67
Index	68

<code>\$.tcc_compiled</code>	<i>Access a compiled FFI symbol</i>
------------------------------	-------------------------------------

Description

Overrides \$ to detect dead pointers after deserialization and recompile transparently from the stored recipe.

Usage

```
## S3 method for class 'tcc_compiled'  
x$name
```

Arguments

- x A tcc_compiled object
- name Symbol name to access

Value

The callable function or metadata field

```
as.character.tcc_cstring
```

Convert a tcc_cstring object to an R string

Description

Convert a tcc_cstring object to an R string

Usage

```
## S3 method for class 'tcc_cstring'
as.character(x, ...)
```

Arguments

x	A tcc_cstring object.
...	Ignored.

Value

A character scalar containing the string value. Returns the cached R copy when available; otherwise reads the current NUL-terminated C string from x\$ptr.

```
blas_lapack_info
```

Report active BLAS/LAPACK runtime information from R

Description

Returns the BLAS/LAPACK runtime details as reported by R itself, plus convenience flags indicating whether Rblas and Rlapack appear available in loaded DLLs/shared objects.

Usage

```
blas_lapack_info()
```

Value

A named list with fields: blas_path, lapack_path, has_rblas, has_rlapack, loaded_dlls.

generate_trampoline	<i>Generate trampoline code for a callback argument</i>
---------------------	---

Description

Generate trampoline code for a callback argument

Usage

```
generate_trampoline(trampoline_name, sig)
```

Arguments

trampoline_name	Name of the trampoline function
sig	Parsed signature

Value

C code string for the trampoline

get_external_ptr_addr	<i>Get the address of an external pointer</i>
-----------------------	---

Description

Extract the memory address from an external pointer as a numeric value. This is primarily useful for debugging and inspection purposes.

Usage

```
get_external_ptr_addr(ptr)
```

Arguments

ptr	An external pointer object (e.g., from <code>tcc_get_symbol()</code>).
-----	---

Value

The memory address as a numeric value.

is_callback_type	<i>Check if a type represents a callback</i>
------------------	--

Description

Check if a type represents a callback

Usage

is_callback_type(type)

Arguments

type Type string to check

Value

Logical

parse_callback_type	<i>Parse callback type specification</i>
---------------------	--

Description

Parse callback type specification

Usage

parse_callback_type(type)

Arguments

type Type string like "callback:double(int,int)"

Value

Parsed signature list or NULL

print.tcc_callback	<i>Print tcc_callback object</i>
--------------------	----------------------------------

Description

Print tcc_callback object

Usage

```
## S3 method for class 'tcc_callback'
print(x, ...)
```

Arguments

x	A tcc_callback object
...	Ignored

Value

The input tcc_callback object, invisibly. Called for its side effect of printing the callback signature, thread-safety flag, and validity status.

print.tcc_compiled	<i>Print tcc_compiled object</i>
--------------------	----------------------------------

Description

Print tcc_compiled object

Usage

```
## S3 method for class 'tcc_compiled'
print(x, ...)
```

Arguments

x	A tcc_compiled object
...	Ignored

Value

The input tcc_compiled object, invisibly. Called for its side effect of printing the compilation output mode and the status of compiled callable symbols.

print.tcc_cstring	<i>Print a tcc_cstring object</i>
-------------------	-----------------------------------

Description

Print a tcc_cstring object

Usage

```
## S3 method for class 'tcc_cstring'
print(x, ...)
```

Arguments

x	A tcc_cstring object.
...	Ignored.

Value

The input tcc_cstring object, invisibly. Called for its side effect of printing the current string value.

print.tcc_ffi	<i>Print tcc_ffi object</i>
---------------	-----------------------------

Description

Print tcc_ffi object

Usage

```
## S3 method for class 'tcc_ffi'
print(x, ...)
```

Arguments

x	A tcc_ffi object
...	Ignored

Value

The input tcc_ffi object, invisibly. Called for its side effect of printing the configured output mode, registered symbols, and selected libraries/include paths.

tcc_add_file	<i>Add a source file to a libtcc state</i>
--------------	--

Description

Add a source file to a libtcc state

Usage

```
tcc_add_file(state, path)
```

Arguments

state	A tcc_state.
path	Path to a C source file.

Value

Integer status code (0 = success).

tcc_add_include_path	<i>Add an include path to a libtcc state</i>
----------------------	--

Description

Add an include path to a libtcc state

Usage

```
tcc_add_include_path(state, path)
```

Arguments

state	A tcc_state.
path	Path to include directory.

Value

Integer status code (0 = success).

tcc_add_library	<i>Add a library to a libtcc state</i>
-----------------	--

Description

Add a library to a libtcc state

Usage

```
tcc_add_library(state, library)
```

Arguments

state	A tcc_state.
library	Library name (e.g., "m" for libm, "R" for libR).

Value

Integer status code (0 = success).

tcc_add_library_path	<i>Add a library path to a libtcc state</i>
----------------------	---

Description

Add a library path to a libtcc state

Usage

```
tcc_add_library_path(state, path)
```

Arguments

state	A tcc_state.
path	Path to library directory.

Value

Integer status code (0 = success).

tcc_add_symbol	<i>Add a symbol to a libtcc state</i>
----------------	---------------------------------------

Description

Add a symbol to a libtcc state

Usage

tcc_add_symbol(state, name, addr)

Arguments

- state A tcc_state.
- name Symbol name.
- addr External pointer address or symbol value.

Value

Integer status code (0 = success).

tcc_add_sysinclude_path	<i>Add a system include path to a libtcc state</i>
-------------------------	--

Description

Add a system include path to a libtcc state

Usage

tcc_add_sysinclude_path(state, path)

Arguments

- state A tcc_state.
- path Path to system include directory.

Value

Integer status code (0 = success).

tcc_bind

*Bind symbols with type specifications***Description**

Define symbols with Bun-style type specifications for API mode. This is the core of the declarative FFI API.

Usage

```
tcc_bind(ffi, ...)
```

Arguments

`ffi` A `tcc_ffi` object

`...` Named list of symbol definitions. Each definition is a list with:

- `args`: List of fixed FFI argument types (e.g., `list("i32", "f64")`)
- `returns`: FFI type for return value (e.g., `"f64", "cstring"`)
- `variadic`: Set `TRUE` for C varargs functions
- `varargs`: Legacy typed variadic tail (exact/prefix mode)
- `varargs_types`: Allowed scalar FFI types for true variadic tails
- `varargs_min`: Minimum number of trailing varargs
- `varargs_max`: Maximum number of trailing varargs (required for true variadic mode, defaults to `varargs_min`)
- `code`: Optional C code for the symbol (for embedded functions)

Callback arguments should use the form `callback:<signature>` (e.g., `callback:double(double)`). The generated trampoline expects a `tcc_callback_ptr(cb)` to the corresponding user-data parameter in the C API. For thread-safe scheduling, use `callback_async:<signature>` which enqueues the call on the main thread and returns a default value immediately.

Value

Updated `tcc_ffi` object (for chaining)

Examples

```
ffi <- tcc_ffi() |>
tcc_bind(
  add = list(args = list("i32", "i32"), returns = "i32"),
  greet = list(args = list("cstring"), returns = "cstring")
)
```

tcc_call_symbol	<i>Call a symbol from a TinyCC state</i>
-----------------	--

Description

With no additional arguments, `tcc_call_symbol()` preserves its historical quick-test behavior: call a zero-argument symbol and box an `int`, `double`, or `void` return value.

Usage

```
tcc_call_symbol(
  .state,
  .NAME,
  ...,
  return = c("int", "double", "void"),
  NAOK = FALSE
)
```

Arguments

<code>.state</code>	A <code>tcc_state</code> . Named <code>state =</code> is also accepted for compatibility with earlier releases.
<code>.NAME</code>	Symbol name to call. Named <code>name =</code> is also accepted for compatibility with earlier releases.
<code>...</code>	Optional arguments for <code>.C()</code> -style pointer calls.
<code>return</code>	One of <code>"int"</code> , <code>"double"</code> , or <code>"void"</code> . If <code>...</code> is present, the only supported value is <code>"void"</code> ; when omitted with <code>...</code> , it defaults to <code>"void"</code> .
<code>NAOK</code>	If <code>FALSE</code> , integer/logical NA and non-finite numeric/complex values are rejected before the call, matching <code>.C()</code> 's default safety check. If <code>TRUE</code> , those values are passed through.

Details

With additional arguments, it uses an R `.C()`-style calling convention: the target C function must be void, each atomic or character R argument is copied to guarded mutable call storage and passed by pointer, and the result is a list of the modified argument values. Supported argument mappings follow R's `.C()` interface: raw as `unsigned char *`, integer/logical as `int *`, numeric as `double *` or `float *` when `attr(x, "Csingle")` is true, complex as `Rcomplex *`, character as `char **`, lists as read-only `SEXP *`, and functions/environments/other R objects as read-only `SEXP`. Up to 65 arguments are supported. Guard bytes around copied buffers are checked after the call to catch simple native underwrites and overwrites; character code may edit string contents in place but must not replace `char *` elements in the `char **` array.

Non-atomic R objects are borrowed for the duration of the call only. C code must not mutate them through this interface, and must call `R_PreserveObject()` if it deliberately stores a `SEXP` beyond the call. This is a low-level convenience interface; for typed scalar returns, explicit zero-copy arrays, ownership metadata, and clearer signatures, prefer `tcc_ffi()`.

Value

For zero-argument scalar calls, the boxed return value (NULL for void). For .C()-style calls, a list mirroring ... with any C-side modifications copied back.

tcc_callback	<i>Register an R function as a callback</i>
--------------	---

Description

Wraps an R function so it can be passed as a C function pointer to compiled code. The callback will be invoked via a trampoline that marshals arguments between C and R.

Usage

```
tcc_callback(fun, signature, threadsafe = FALSE)
```

Arguments

fun	An R function to be called from C
signature	C function signature string (e.g., "double (*)(int, double)")
threadsafe	Whether to enable thread-safe invocation (experimental)

Details

Thread safety: callbacks are executed on the R main thread only. Invoking a callback from a worker thread is unsupported and may crash R. The threadsafe flag is currently informational only.

If a callback raises an error, a warning is emitted and a type-appropriate default value is returned.

When binding callbacks with `tcc_bind()`, use a `callback:<signature>` argument type so a synchronous trampoline is generated. The trampoline expects a `void*` user-data pointer as its first argument; pass `tcc_callback_ptr(cb)` as the user-data argument to the C API. For thread-safe usage from worker threads, use `callback_async:<signature>` which schedules the call on the main thread and returns a default value.

Pointer arguments (e.g., `double*`, `int*`) are passed as external pointers. Lengths must be supplied separately if needed.

The return type may be any scalar type supported by the FFI mappings (e.g., `i32`, `f64`, `bool`, `cstring`), or `SEXP` to return an R object directly.

Callback lifetime: callbacks are eventually released by finalizers and package unload. Call `tcc_callback_close()` when you want deterministic invalidation and earlier release of the preserved R function.

Value

A `tcc_callback` object (externalptr wrapper)

tcc_callback_async_drain

Drain the async callback queue

Description

Execute any pending async callbacks immediately on the main R thread. Normally callbacks fire automatically via R's event loop (input handler on POSIX, message pump on Windows), so explicit draining is only needed in test harnesses or tight batch loops that never yield to R's event loop.

Usage

```
tcc_callback_async_drain()
```

Details

TCC-compiled C code that is known to be running on the main R thread can call `RC_callback_async_drain_c()` directly instead of returning to R. Functions bound with `callback_async:*` arguments are normally executed on a worker by the generated wrapper while the main thread drains, so user code in that target function should not assume it is itself on the main thread.

Value

NULL (invisible)

tcc_callback_async_schedule

Schedule a callback to run on the main thread

Description

Enqueue a callback for main-thread execution. Arguments must be basic scalars or external pointers.

Usage

```
tcc_callback_async_schedule(callback, args = list())
```

Arguments

callback	A <code>tcc_callback</code> object
args	List of arguments to pass to the callback

Value

NULL (invisible)

tcc_callback_close	<i>Close/unregister a callback</i>
--------------------	------------------------------------

Description

Invalidates a callback immediately, releases the preserved R function reference, and cleans up callback resources as early as possible. This is recommended for deterministic lifetime management, but callbacks are also eventually released by finalizers if you simply drop all references.

Usage

```
tcc_callback_close(callback)
```

Arguments

callback	A tcc_callback object returned by tcc_callback()
----------	--

Value

NULL (invisible)

tcc_callback_ptr	<i>Get the C-compatible function pointer</i>
------------------	--

Description

Returns an external pointer that can be passed to compiled C code as user data for trampolines. Keep this handle (and the original tcc_callback) alive for as long as C may call back. The pointer handle keeps the underlying token storage alive until it is garbage collected. Closing the original callback still invalidates the callback registry entry, so C must not continue invoking it after tcc_callback_close().

Usage

```
tcc_callback_ptr(callback)
```

Arguments

callback	A tcc_callback object
----------	-----------------------

Details

Pointer arguments and return values are treated as external pointers. Use tcc_read_bytes(), tcc_read_u8(), or tcc_read_f64() to inspect pointed data when needed.

Value

An external pointer (address of the callback token)

tcc_callback_valid	<i>Check if callback is still valid</i>
--------------------	---

Description

Check if callback is still valid

Usage

```
tcc_callback_valid(callback)
```

Arguments

callback	A tcc_callback object
----------	-----------------------

Value

Logical indicating if callback can be invoked

tcc_compile	<i>Compile FFI bindings</i>
-------------	-----------------------------

Description

Compile the defined symbols into callable functions. This generates C wrapper code and compiles it with TinyCC.

Usage

```
tcc_compile(ffi, verbose = FALSE)
```

Arguments

ffi	A tcc_ffi object
verbose	Print compilation info

Value

A tcc_compiled object with callable functions

tcc_compile_string	<i>Compile C code from a character string</i>
--------------------	---

Description

Compile C code from a character string

Usage

```
tcc_compile_string(state, code)
```

Arguments

state	A tcc_state.
code	C source code string.

Value

Integer status code (0 = success).

tcc_container_of	<i>Generate container_of helper for struct member</i>
------------------	---

Description

Creates a function that recovers the parent struct pointer from a pointer to one of its members. This is the classic Linux kernel container_of macro made accessible from R.

Usage

```
tcc_container_of(ffl, struct_name, member_name)
```

Arguments

ffl	A tcc_ffl object
struct_name	Struct name
member_name	Member field name to compute offset from

Value

Updated tcc_ffl object

Examples

```
## Not run:
ffi <- tcc_ffi() |>
  tcc_struct("student", list(id = "i32", marks = "i32")) |>
  tcc_container_of("student", "marks") # Creates struct_student_from_marks()

## End(Not run)
```

tcc_cstring	Create a C-style string pointer
-------------	---------------------------------

Description

Convert R character strings to C-style null-terminated string pointers. This handles UTF-8 encoding and null termination automatically.

Usage

```
tcc_cstring(str)
```

Arguments

str	Character string
-----	------------------

Value

An external pointer tagged "rtinycc_owned" pointing to a malloc'd copy of the string. Freed on garbage collection or via [tcc_free\(\)](#).

tcc_cstring_object	CString S3 Class
--------------------	------------------

Description

Wrapper around a C string pointer with an optional cached R copy. Ownership follows the underlying external pointer; this wrapper does not add finalizer or freeing behavior on top of that pointer.

Usage

```
tcc_cstring_object(ptr, clone = TRUE, owned = FALSE)
```

Arguments

ptr	External pointer to C string
clone	Whether to clone the string immediately (safe for R use)
owned	Currently unused. Reserved for future finalizer support.

Value

A tcc_cstring object

tcc_data_ptr	<i>Dereference a pointer-to-pointer</i>
--------------	---

Description

Treats ptr_ref as a pointer to a pointer and returns the pointed address as an external pointer. This is useful for fields like void** or T**.

Usage

```
tcc_data_ptr(ptr_ref)
```

Arguments

ptr_ref	External pointer to a pointer value (e.g., address of a field).
---------	---

Value

An external pointer tagged "rtinyc_borrowed". Not owned by Rtinyc and never freed on garbage collection. Do not pass to [tcc_free\(\)](#).

tcc_enum	<i>Declare enum for FFI helper generation</i>
----------	---

Description

Generate R-callable helpers for enum constants and type conversions. The enum must be defined in a header.

Usage

```
tcc_enum(ffi, name, constants = NULL, export_constants = FALSE)
```

Arguments

ffi	A tcc_ffi object
name	Enum name (as defined in C header)
constants	Character vector of constant names to export
export_constants	Whether to export enum constants as R functions

Value

Updated tcc_ffi object

Examples

```
## Not run:
ffi <- tcc_ffi() |>
  tcc_header("#include <errors.h>") |>
  tcc_enum("error_code", constants = c("OK", "ERROR"), export_constants = TRUE)

## End(Not run)
```

tcc_ffi	Create a new FFI compilation context
---------	--------------------------------------

Description

Initialize a Bun-style FFI context for API-mode compilation. This is the entry point for the modern FFI API.

Usage

```
tcc_ffi()
```

Value

A tcc_ffi object with chaining support

Examples

```
ffi <- tcc_ffi()
```

tcc_field_addr	Generate field address getter helpers
----------------	---------------------------------------

Description

Creates functions that return pointers to specific struct fields. Useful for passing field pointers to C functions or for container_of.

Usage

```
tcc_field_addr(ffi, struct_name, fields)
```

Arguments

ffi	A tcc_ffi object
struct_name	Struct name
fields	Character vector of field names

Value

Updated tcc_ffi object

Examples

```
## Not run:
ffi <- tcc_ffi() |>
  tcc_struct("point", list(x = "f64", y = "f64")) |>
  tcc_field_addr("point", c("x", "y")) # point_x_addr(), point_y_addr()

## End(Not run)
```

tcc_free	<i>Free owned memory</i>
----------	--------------------------

Description

Free memory whose external pointer is tagged "rtinyc-owned" (e.g. from [tcc_malloc\(\)](#) or [tcc_cstring\(\)](#)). Errors on struct pointers (use the generated struct_<name>_free()) or borrowed pointers from [tcc_data_ptr\(\)](#).

Usage

```
tcc_free(ptr)
```

Arguments

ptr	External pointer to free
-----	--------------------------

Value

NULL.

tcc_generate_bindings *Generate bindings from header declarations*

Description

Generate bindings from header declarations

Usage

```
tcc_generate_bindings(
  ffi = NULL,
  header,
  mapper = tcc_map_c_type_to_ffi,
  functions = TRUE,
  structs = TRUE,
  unions = TRUE,
  enums = TRUE,
  globals = TRUE,
  bitfield_type = "u8",
  include_bitfields = TRUE
)
```

Arguments

ffi	A tcc_ffi object. If NULL, a new one is created.
header	Character scalar containing C declarations.
mapper	Function to map C types to FFI types.
functions	Logical; generate tcc_bind() specs for functions.
structs	Logical; generate tcc_struct() helpers.
unions	Logical; generate tcc_union() helpers.
enums	Logical; generate tcc_enum() helpers.
globals	Logical; generate tcc_global() getters/setters.
bitfield_type	FFI type to use for bitfields.
include_bitfields	Whether to include bitfields.

Value

Updated tcc_ffi object.

Examples

```
## Not run:
header <- "double sqrt(double x); struct point { double x; double y; };"
ffi <- tcc_generate_bindings(tcc_ffi(), header)

## End(Not run)
```

tcc_get_symbol	<i>Get a symbol pointer from a libtcc state</i>
----------------	---

Description

Get a symbol pointer from a libtcc state

Usage

```
tcc_get_symbol(state, name)
```

Arguments

state	A tcc_state.
name	Symbol name to look up.

Value

External pointer of class tcc_symbol.

tcc_global	<i>Declare a global variable getter</i>
------------	---

Description

Register a global C symbol so the compiled object exposes getter/setter functions `global_<name>_get()` and `global_<name>_set()`.

Usage

```
tcc_global(ffl, name, type)
```

Arguments

ffl	A tcc_ffl object
name	Global symbol name
type	FFI type for the global (scalar types only)

Details

Globals are limited to scalar FFI types. Array types are rejected. Scalar conversions follow the same rules as wrapper arguments:

- Integer inputs (i8, i16, i32, u8, u16) must be finite and within range; NA values error.
- Large integer types (i64, u32, u64) are mediated through R numeric (double). Values must be integer-valued and within range; for i64/u64 only exact integers up to 2^{53} are accepted.
- Getter wrappers for i64/u64 warn when the stored value exceeds R's exact integer range for numeric vectors.
- bool rejects NA logicals.

Ownership notes:

- ptr globals store the raw address from an external pointer. If the external pointer owns memory, keep it alive; otherwise the pointer may be freed while the global still points to it.
- cstring globals store a borrowed pointer to R's string data (UTF-8 translation). Do not free it; for C-owned strings prefer a ptr global and manage lifetime explicitly (e.g., with `tcc_cstring()`).

Value

Updated `tcc_ffi` object (for chaining)

Note

Global helpers are generated inside the compiled TCC unit. Recompiling creates a new instance of the global variable; existing compiled objects continue to refer to their own copy.

Examples

```
ffi <- tcc_ffi() |>
  tcc_source("int global_counter = 7;") |>
  tcc_global("global_counter", "i32") |>
  tcc_compile()
ffi$global_global_counter_get()
```

tcc_header

Add C headers

Description

Add C headers

Usage

```
tcc_header(ffi, header)
```

Arguments

ffi	A tcc_ffi object
header	Header string or include directive

Value

Updated tcc_ffi object (for chaining)

tcc_include	<i>Add include path to FFI context</i>
-------------	--

Description

Add include path to FFI context

Usage

```
tcc_include(ffi, path)
```

Arguments

ffi	A tcc_ffi object
path	Include directory path

Value

Updated tcc_ffi object (for chaining)

tcc_include_paths	<i>TinyCC include search paths</i>
-------------------	------------------------------------

Description

Returns the include directories used by the bundled TinyCC (top-level include and lib/tcc/include).

Usage

```
tcc_include_paths()  
  
tcc_sysinclude_paths()
```

Value

A character vector of include directories.

tcc_introspect	<i>Enable introspection helpers</i>
----------------	-------------------------------------

Description

Generates sizeof, alignof, and offsetof helper functions for structs, unions, and enums. Useful for debugging or when you need to know C layout information from R.

Usage

```
tcc_introspect(ffi)
```

Arguments

ffi	A tcc_ffi object
-----	------------------

Value

Updated tcc_ffi object

tcc_library	<i>Add library to link against</i>
-------------	------------------------------------

Description

Add library to link against

Usage

```
tcc_library(ffi, library)
```

Arguments

ffi	A tcc_ffi object
library	Library name (e.g., "m", "sqlite3") or a path to a shared library (e.g., "libm.so.6"). When a path or platform library file name is provided, the library directory is added automatically and TinyCC is asked to link that exact file name. This keeps versioned runtime libraries such as libm.so.6 distinct from generic linker names such as m/libm.so.

Value

Updated tcc_ffi object (for chaining)

tcc_library_path	<i>Add library path to FFI context</i>
------------------	--

Description

Add library path to FFI context

Usage

```
tcc_library_path(ffi, path)
```

Arguments

ffi	A tcc_ffi object
path	Library directory path

Value

Updated tcc_ffi object (for chaining)

tcc_link	<i>Link an external shared library with Bun-style FFI bindings</i>
----------	--

Description

Link a system library (like libsqlite3) and generate type-safe wrappers automatically using TinyCC JIT compilation (API mode). Unlike dlopen(), this uses TinyCC to compile bindings that handle type conversion between R and C automatically.

Usage

```
tcc_link(  
  path,  
  symbols,  
  headers = NULL,  
  libs = character(0),  
  lib_paths = character(0),  
  include_paths = character(0),  
  user_code = NULL,  
  verbose = FALSE  
)
```

Arguments

path	Library short name (e.g., "m", "sqlite3") or full path to the shared library. Short names stay on the normal linker-name path (-l<name>). File names such as libm.so.6 or full paths are resolved through the configured library search paths when needed and linked as exact files rather than collapsed to generic names like m.
symbols	Named list of symbol definitions with: • args: List of FFI types for arguments • returns: FFI type for return value
headers	Optional C headers to include
libs	Library names to link (e.g., "sqlite3")
lib_paths	Additional library search paths
include_paths	Additional include search paths
user_code	Optional custom C code to include in the compilation
verbose	Print debug information

Value

A tcc_compiled object with callable functions

Examples

```
## Not run:
# Link SQLite with type-safe bindings
sqlite <- tcc_link(
  "libsqlite3.so",
  symbols = list(
    sqlite3_libversion = list(args = list(), returns = "cstring"),
    sqlite3_open = list(args = list("cstring", "ptr"), returns = "i32")
  ),
  libs = "sqlite3"
)

# Call directly - type conversion happens automatically
sqlite$sqlite3_libversion()

# Example with custom user code for helper functions
math_with_helpers <- tcc_link(
  "m",
  symbols = list(
    sqrt = list(args = list("f64"), returns = "f64"),
    safe_sqrt = list(args = list("f64"), returns = "f64")
  ),
  user_code = "
    #include <math.h>

    // Helper function that validates input before calling sqrt
    double safe_sqrt(double x) {
```

```

        if (x < 0) {
            return NAN;
        }
        return sqrt(x);
    }
    ",
    libs = "m"
)
math_with_helpers$safe_sqrt(16.0)
math_with_helpers$safe_sqrt(-4.0) # Returns NaN for negative input

## End(Not run)

```

tcc_list_symbols	<i>List symbols known to a libtcc state</i>
------------------	---

Description

Return the global symbols currently reported by libtcc for a state. This is a best-effort symbol-table inspection helper for compiled/linked TCC states, not a portable exhaustive symbol enumerator, not a DLL export scanner, and not a C signature discovery API. Platform backends may omit symbols that are still resolvable with [tcc_get_symbol\(\)](#). For meaningful runtime addresses, call it after [tcc_relocate\(\)](#).

Usage

```
tcc_list_symbols(state)
```

Arguments

state A tcc_state.

Value

A data frame with columns name and address, where address is a hexadecimal character string.

tcc_malloc	<i>Allocate memory buffer</i>
------------	-------------------------------

Description

Allocate a memory buffer of specified size, equivalent to C malloc. Returns an external pointer that can be passed to FFI functions.

Usage

```
tcc_malloc(size)
```

Arguments

size Number of bytes to allocate

Value

An external pointer tagged "rtinyc Owned" with an R finalizer. Freed on garbage collection or explicitly via `tcc_free()`.

tcc_map_c_type_to_ffi *Map a C type string to an Rtinyc FFI type*

Description

Map a C type string to an Rtinyc FFI type

Usage

```
tcc_map_c_type_to_ffi(c_type)
```

Arguments

c_type C type string (e.g., "int", "double", "char *").

Details

This mapper is intentionally conservative for pointer types. `char*` is treated as a raw pointer (`ptr`) because C does not guarantee NUL-terminated strings. If you know the API expects a C string, map it explicitly to `cstring` in your custom mapper.

Value

A single FFI type string.

Examples

```
## Not run:
tcc_map_c_type_to_ffi("int")
tcc_map_c_type_to_ffi("const char *")

## End(Not run)
```

tcc_null_ptr	Create a <i>NULL</i> pointer
--------------	------------------------------

Description

Creates a *NULL* pointer equivalent for use with FFI functions that expect optional pointer arguments.

Usage

```
tcc_null_ptr()
```

Value

An external pointer with *NULL* address

tcc_options	Add <i>TinyCC</i> compiler options to FFI context
-------------	---

Description

Append raw options that are passed to `tcc_set_options()` before compiling generated wrappers (for example `"-O2"` or `"-Wall"`).

Usage

```
tcc_options(ffi, options)
```

Arguments

ffi	A <code>tcc_ffi</code> object
options	Character vector of option fragments

Value

Updated `tcc_ffi` object (for chaining)

tcc_output	<i>Set output type for FFI compilation</i>
------------	--

Description

Set output type for FFI compilation

Usage

```
tcc_output(ffi, output = c("memory", "dll", "exe"))
```

Arguments

ffi	A tcc_ffi object
output	One of "memory", "dll", "exe"

Value

Updated tcc_ffi object (for chaining)

tcc_path	<i>Locate the TinyCC executable</i>
----------	-------------------------------------

Description

Returns the platform-specific tcc binary path (or tcc.exe on Windows), preferring the bundled installation.

Usage

```
tcc_path()
```

Value

A character scalar path.

tcc_prefix	<i>TinyCC paths</i>
------------	---------------------

Description

Helpers to locate the bundled tinycc installation after the package is installed.

Usage

```
tcc_prefix()

tcc_lib_path()

tcc_lib_paths()

tcc_include_path()

tcc_bin_path()

tcc_cli()
```

Value

A character scalar path.

tcc_ptr_addr	<i>Get pointer address as integer</i>
--------------	---------------------------------------

Description

Get the numeric address of an external pointer, useful for debugging and when APIs require pointer addresses as integers. Optional hex mode available.

Usage

```
tcc_ptr_addr(ptr, hex = FALSE)
```

Arguments

ptr	External pointer
hex	Whether to display in hexadecimal (default: FALSE)

Value

Character representation of pointer address (hex if requested, decimal otherwise)

`tcc_ptr_free_set_null` *Free the pointed memory and set to NULL*

Description

Frees the memory pointed to by `ptr_ref` and sets the pointer to NULL. Use this only when the pointed memory is not already owned by another external pointer with its own finalizer.

Usage

```
tcc_ptr_free_set_null(ptr_ref)
```

Arguments

`ptr_ref` External pointer to a pointer value.

Value

The updated pointer reference (invisibly).

`tcc_ptr_is_null` *Check whether an external pointer is NULL*

Description

Returns TRUE if the external pointer address is NULL, FALSE otherwise.

Usage

```
tcc_ptr_is_null(ptr)
```

Arguments

`ptr` External pointer

Value

Logical scalar

tcc_ptr_is_owned	<i>Check for the "rtinyc_owned" tag</i>
------------------	---

Description

Returns TRUE only for pointers created by `tcc_malloc()` or `tcc_cstring()`. Struct pointers (tagged "struct_<name>") and borrowed pointers return FALSE.

Usage

```
tcc_ptr_is_owned(ptr)
```

Arguments

ptr	External pointer
-----	------------------

Value

Logical scalar

tcc_ptr_set	<i>Set a pointer-to-pointer value</i>
-------------	---------------------------------------

Description

Assigns the address in ptr_value to the location pointed to by ptr_ref.

Usage

```
tcc_ptr_set(ptr_ref, ptr_value)
```

Arguments

ptr_ref	External pointer to a pointer value (e.g., address of a field).
ptr_value	External pointer to store.

Value

The updated pointer reference (invisibly).

`tcc_ptr_utils`*Pointer and Buffer Utilities for FFI*

Description

Generic helper functions for common FFI operations inspired by Bun's FFI. These utilities handle pointer creation, buffer management, and memory operations that are commonly needed when working with external libraries.

Value

No return value. This is a documentation topic that groups the pointer and buffer utility functions described below.

`tcc_read_bytes`*Read raw bytes from a pointer*

Description

Read a fixed number of bytes from an external pointer into a raw vector.

Usage

```
tcc_read_bytes(ptr, nbytes)
```

Arguments

<code>ptr</code>	External pointer
<code>nbytes</code>	Number of bytes to read

Value

Raw vector

tcc_read_cstring	<i>Read C-style string from pointer</i>
------------------	---

Description

Convert a C-style null-terminated string pointer back to R character string. Handles UTF-8 decoding automatically.

Usage

```
tcc_read_cstring(
  ptr,
  max_bytes = NULL,
  null_action = c("na", "empty", "error")
)
```

Arguments

ptr	External pointer to C string
max_bytes	Optional maximum number of bytes to read (fixed-length read).
null_action	Behavior when ptr is NULL: one of "na", "empty", "error". Only effective when max_bytes is provided; without it a NULL pointer returns "".

Value

Character string, or NA/"" for NULL pointers depending on null_action.

tcc_read_f32	<i>Read 32-bit float</i>
--------------	--------------------------

Description

Read 32-bit float

Usage

```
tcc_read_f32(ptr, offset = 0L)
```

Arguments

ptr	External pointer
offset	Byte offset from ptr (scalar interface). Ignored when n is supplied.

Value

Numeric scalar (promoted to double).

tcc_read_f64	<i>Read 64-bit doubles from a pointer</i>
--------------	---

Description

Read 64-bit doubles from a pointer

Usage

tcc_read_f64(ptr, n = NULL, offset = 0L)

Arguments

- ptr External pointer
- n Number of values to read (legacy vectorised interface). If provided, reads n consecutive f64 values starting at byte 0.
- offset Byte offset from ptr (scalar interface). Ignored when n is supplied.

Value

Numeric scalar (offset form) or numeric vector (n form).

tcc_read_i16	<i>Read signed 16-bit integer</i>
--------------	-----------------------------------

Description

Read signed 16-bit integer

Usage

tcc_read_i16(ptr, offset = 0L)

Arguments

- ptr External pointer
- offset Byte offset from ptr (scalar interface). Ignored when n is supplied.

Value

Integer scalar

tcc_read_i32	<i>Read signed 32-bit integers from a pointer</i>
--------------	---

Description

Read signed 32-bit integers from a pointer

Usage

```
tcc_read_i32(ptr, n = NULL, offset = 0L)
```

Arguments

ptr	External pointer
n	Number of values to read (legacy vectorised interface). If provided, reads n consecutive i32 values starting at byte 0.
offset	Byte offset from ptr (scalar interface). Ignored when n is supplied.

Value

Integer scalar (offset form) or integer vector (n form).

tcc_read_i64	<i>Read signed 64-bit integer</i>
--------------	-----------------------------------

Description

Read signed 64-bit integer

Usage

```
tcc_read_i64(ptr, offset = 0L)
```

Arguments

ptr	External pointer
offset	Byte offset from ptr (scalar interface). Ignored when n is supplied.

Value

Numeric scalar (double, exact up to 2^{53}).

tcc_read_i8	<i>Read signed 8-bit integer</i>
-------------	----------------------------------

Description

Read signed 8-bit integer

Usage

tcc_read_i8(ptr, offset = 0L)

Arguments

- ptr External pointer
- offset Byte offset from ptr (scalar interface). Ignored when n is supplied.

Value

Integer scalar

tcc_read_ptr	<i>Read a pointer at byte offset</i>
--------------	--------------------------------------

Description

Dereferences a void* at the given byte offset from ptr. Equivalent to *(void**)(ptr + offset). The returned pointer is tagged "rtinycc_borrowed" and will not be freed by the garbage collector.

Usage

tcc_read_ptr(ptr, offset = 0L)

Arguments

- ptr External pointer
- offset Byte offset from ptr (scalar interface). Ignored when n is supplied.

Value

External pointer

tcc_read_u16	<i>Read unsigned 16-bit integer</i>
--------------	-------------------------------------

Description

Read unsigned 16-bit integer

Usage

tcc_read_u16(ptr, offset = 0L)

Arguments

- ptr External pointer
- offset Byte offset from ptr (scalar interface). Ignored when n is supplied.

Value

Integer scalar

tcc_read_u32	<i>Read unsigned 32-bit integer</i>
--------------	-------------------------------------

Description

Read unsigned 32-bit integer

Usage

tcc_read_u32(ptr, offset = 0L)

Arguments

- ptr External pointer
- offset Byte offset from ptr (scalar interface). Ignored when n is supplied.

Value

Numeric scalar (double, exact up to 2^32-1).

tcc_read_u64	<i>Read unsigned 64-bit integer</i>
--------------	-------------------------------------

Description

Read unsigned 64-bit integer

Usage

```
tcc_read_u64(ptr, offset = 0L)
```

Arguments

- ptr External pointer
- offset Byte offset from ptr (scalar interface). Ignored when n is supplied.

Value

Numeric scalar (double, exact up to 2⁵³).

tcc_read_u8	<i>Read unsigned 8-bit values from a pointer</i>
-------------	--

Description

Read unsigned 8-bit values from a pointer

Usage

```
tcc_read_u8(ptr, n = NULL, offset = 0L)
```

Arguments

- ptr External pointer
- n Number of values to read (legacy vectorised interface). If provided, reads n consecutive u8 values starting at byte 0.
- offset Byte offset from ptr (scalar interface). Ignored when n is supplied.

Value

Integer scalar (offset form) or integer vector (n form).

tcc_recompile	<i>Recompile a tcc_compiled object</i>
---------------	--

Description

Explicitly recompile from the stored FFI recipe. Useful after deserialization (`readRDS`, `unserialize`) or to force a fresh compilation.

Usage

```
tcc_recompile(compiled)
```

Arguments

compiled	A <code>tcc_compiled</code> object
----------	------------------------------------

Value

The recompiled `tcc_compiled` object (invisibly, same environment)

tcc_relocate	<i>Relocate compiled code</i>
--------------	-------------------------------

Description

Relocate compiled code

Usage

```
tcc_relocate(state)
```

Arguments

state	A <code>tcc_state</code> .
-------	----------------------------

Value

Integer status code (0 = success).

tcc_run_cli	<i>Run the tinycc CLI</i>
-------------	---------------------------

Description

Run the tinycc CLI

Usage

```
tcc_run_cli(args = character(), tcc_path = check_cli_exists())
```

Arguments

args	Character vector of CLI arguments (e.g., c("-c", file, "-o", out)).
tcc_path	Optional path to the tcc binary; defaults to the bundled CLI.

Value

Integer status from system2().

tcc_set_options	<i>Apply raw TinyCC options to a libtcc state</i>
-----------------	---

Description

Passes options directly to tcc_set_options() for the given state.

Usage

```
tcc_set_options(state, options)
```

Arguments

state	A tcc_state.
options	Character scalar of options (for example "-O2 -Wall").

Value

Integer status code (0 on success; negative on parse error).

tcc_source	<i>Add C source code</i>
------------	--------------------------

Description

Add C source code

Usage

```
tcc_source(ffi, code)
```

Arguments

ffi	A tcc_ffi object
code	C source code string

Value

Updated tcc_ffi object (for chaining)

tcc_state	<i>Create a libtcc state</i>
-----------	------------------------------

Description

Initialize a libtcc compilation state, optionally pointing at the bundled include/lib paths.

Usage

```
tcc_state(  
    output = c("memory", "obj", "dll", "exe", "preprocess"),  
    include_path = tcc_include_paths(),  
    lib_path = tcc_lib_paths()  
)
```

Arguments

output	Output type: one of "memory", "obj", "dll", "exe", "preprocess".
include_path	Path(s) to headers; defaults to the bundled include dirs.
lib_path	Path(s) to libraries; defaults to the bundled lib dirs (lib and lib/tcc).

Value

An external pointer of class tcc_state.

tcc_struct	<i>Declare struct for FFI helper generation</i>
------------	---

Description

Generate R-callable helpers for struct allocation, field access, and pointer management. The struct must be defined in a header.

Usage

```
tcc_struct(ffi, name, accessors)
```

Arguments

ffi	A tcc_ffi object
name	Struct name (as defined in C header)
accessors	Named list of field accessors where names are field names and values are FFI types (e.g., list(x="f64", y="f64")). Named nested struct fields can use "struct:<name>" to generate borrowed nested-view getters and copy-in setters (for example child = "struct:child").

Value

Updated tcc_ffi object

Examples

```
## Not run:
ffi <- tcc_ffi() |>
  tcc_header("#include <point.h>") |>
  tcc_struct("point", list(x = "f64", y = "f64", id = "i32"))

## End(Not run)
```

tcc_struct_raw_access	<i>Enable raw byte access for struct</i>
-----------------------	--

Description

Generates helper functions to read/write raw bytes from struct memory. Useful for bitwise operations, debugging, or manual serialization.

Usage

```
tcc_struct_raw_access(ffi, struct_name)
```


Arguments

ffi	A tcc_ffi object
struct_name	Struct name

Value

Updated tcc_ffi object

tcc_symbol_is_valid	<i>Check if a tcc_symbol external pointer is valid</i>
---------------------	--

Description

Check if a tcc_symbol external pointer is valid

Usage

```
tcc_symbol_is_valid(ptr)
```

Arguments

ptr	External pointer from tcc_get_symbol().
-----	---

Value

TRUE if the pointer address is non-null, FALSE otherwise.

tcc_treesitter_bindings	<i>Generate bindings from a header</i>
-------------------------	--

Description

Generate bindings from a header

Usage

```
tcc_treesitter_bindings(
    header,
    mapper = tcc_map_c_type_to_ffi,
    ffi = NULL,
    functions = TRUE,
    structs = FALSE,
    unions = FALSE,
    enums = FALSE,
```

```

    globals = FALSE,
    bitfield_type = "u8",
    include_bitfields = TRUE
  )

```

Arguments

header	Character scalar containing C declarations.
mapper	Function to map C types to FFI types.
ffi	Optional tcc_ffi object. When provided, returns an updated FFI object with generated bindings.
functions	Logical; generate tcc_bind() specs for functions.
structs	Logical; generate tcc_struct() helpers.
unions	Logical; generate tcc_union() helpers.
enums	Logical; generate tcc_enum() helpers.
globals	Logical; generate tcc_global() getters/setters.
bitfield_type	FFI type to use for bitfields.
include_bitfields	Whether to include bitfields.

Value

Named list suitable for tcc_bind() when ffi is NULL, otherwise an updated tcc_ffi object.

Examples

```

## Not run:
header <- "double sqrt(double x);"
symbols <- tcc_treesitter_bindings(header)

## End(Not run)

```

```
tcc_treesitter_defines
```

Extract macro defines from a header file

Description

Extract macro defines from a header file

Usage

```

tcc_treesitter_defines(
  file,
  use_cpp = TRUE,
  cc = treesitter.c::r_cc(),
  ccflags = NULL
)

```

Arguments

file	Path to a header file.
use_cpp	Logical; use the C preprocessor if available.
cc	Compiler string; passed to system2() if use_cpp = TRUE.
ccflags	Additional flags for the compiler.

Value

Character vector of macro names defined in file.

Examples

```
## Not run:
tcc_treesitter_defines("/usr/include/math.h")

## End(Not run)
```

tcc_treesitter_enum_bindings

Apply tcc_enum() bindings from a header

Description

Apply tcc_enum() bindings from a header

Usage

```
tcc_treesitter_enum_bindings(ffl, header, constants = NULL)
```

Arguments

ffl	A tcc_ffl object.
header	Character scalar containing C declarations.
constants	Named list of enum constants.

Value

Updated tcc_ffl object.

Examples

```
## Not run:
header <- "enum status { OK = 0, ERR = 1 };"
ffl <- tcc_ffl()
ffl <- tcc_treesitter_enum_bindings(ffl, header, constants = list(status = c("OK", "ERR")))

## End(Not run)
```

`tcc_treesitter_enum_members`*Parse enum members with treesitter.c*

Description

Parse enum members with treesitter.c

Usage

```
tcc_treesitter_enum_members(header, ...)
```

Arguments

<code>header</code>	Character scalar containing C declarations.
<code>...</code>	Additional arguments passed to <code>treesitter.c::get_enum_members_from_root()</code> .

Value

A data frame of enum members.

Examples

```
## Not run:
header <- "enum status { OK = 0, ERR = 1 };"
tcc_treesitter_enum_members(header)

## End(Not run)
```

`tcc_treesitter_enums` *Parse enum declarations with treesitter.c*

Description

Parse enum declarations with treesitter.c

Usage

```
tcc_treesitter_enums(header, ...)
```

Arguments

<code>header</code>	Character scalar containing C declarations.
<code>...</code>	Additional arguments passed to <code>treesitter.c::get_enum_nodes()</code> .

Value

A data frame of enum nodes.

Examples

```
## Not run:
header <- "enum status { OK = 0, ERR = 1 };"
tcc_treesitter_enums(header)

## End(Not run)
```

tcc_treesitter_functions

Parse function declarations with treesitter.c

Description

Parse function declarations with treesitter.c

Usage

```
tcc_treesitter_functions(header, ...)
```

Arguments

header	Character scalar containing C declarations.
...	Additional arguments passed to <code>treesitter.c::get_function_nodes()</code> .

Value

A data frame of function nodes.

Examples

```
## Not run:
header <- "double sqrt(double x);"
tcc_treesitter_functions(header)

## End(Not run)
```

tcc_treesitter_global_types

Parse global declarations with types using treesitter.c

Description

Parse global declarations with types using treesitter.c

Usage

```
tcc_treesitter_global_types(header, ...)
```

Arguments

header	Character scalar containing C declarations.
...	Additional arguments passed to <code>treesitter.c::get_globals_with_types_from_root()</code> .

Value

A data frame of global names and C types.

Examples

```
## Not run:
header <- "int global_counter;"
tcc_treesitter_global_types(header)

## End(Not run)
```

tcc_treesitter_globals

Parse global declarations with treesitter.c

Description

Parse global declarations with treesitter.c

Usage

```
tcc_treesitter_globals(header, ...)
```

Arguments

header	Character scalar containing C declarations.
...	Additional arguments passed to <code>treesitter.c::get_globals_from_root()</code> .

Value

A data frame of global names.

Examples

```
## Not run:
header <- "int global_counter;"
tcc_treesitter_globals(header)

## End(Not run)
```

```
tcc_treesitter_struct_accessors
```

Generate tcc_struct() accessors from header structs

Description

Generate tcc_struct() accessors from header structs

Usage

```
tcc_treesitter_struct_accessors(
  header,
  mapper = tcc_map_c_type_to_ffi,
  bitfield_type = "u8",
  include_bitfields = TRUE
)
```

Arguments

header	Character scalar containing C declarations.
mapper	Function to map C types to FFI types.
bitfield_type	FFI type to use for bitfields.
include_bitfields	Whether to include bitfields.

Value

Named list of accessors by struct name. Bitfields are returned as lists with type, bitfield = TRUE, and width. Named nested struct fields are returned as "struct:<name>"; ambiguous or anonymous nested structs fall back to "ptr".

Examples

```
## Not run:
header <- "struct point { double x; double y; };"
tcc_treesitter_struct_accessors(header)

## End(Not run)
```

```
tcc_treesitter_struct_bindings
```

Apply tcc_struct() bindings from a header

Description

Apply tcc_struct() bindings from a header

Usage

```
tcc_treesitter_struct_bindings(ffi, header, ...)
```

Arguments

ffi	A tcc_ffi object.
header	Character scalar containing C declarations.
...	Passed to tcc_treesitter_struct_accessors().

Value

Updated tcc_ffi object.

Examples

```
## Not run:
header <- "struct point { double x; double y; };"
ffi <- tcc_ffi()
ffi <- tcc_treesitter_struct_bindings(ffi, header)

## End(Not run)
```

```
tcc_treesitter_struct_members
```

Parse struct members (including bitfields) with treesitter.c

Description

Parse struct members (including bitfields) with treesitter.c

Usage

```
tcc_treesitter_struct_members(header, ...)
```

Arguments

header	Character scalar containing C declarations.
...	Additional arguments passed to treesitter.c::get_struct_members().

Value

A data frame of struct members.

Examples

```
## Not run:
header <- "struct point { double x; double y; };"
tcc_treesitter_struct_members(header)

## End(Not run)
```

tcc_treesitter_structs

Parse struct declarations with treesitter.c

Description

Parse struct declarations with treesitter.c

Usage

```
tcc_treesitter_structs(header, ...)
```

Arguments

header	Character scalar containing C declarations.
...	Additional arguments passed to <code>treesitter.c::get_struct_nodes()</code> .

Value

A data frame of struct nodes.

Examples

```
## Not run:
header <- "struct point { double x; double y; };"
tcc_treesitter_structs(header)

## End(Not run)
```

tcc_treesitter_union_accessors

Generate tcc_union() accessors from header unions

Description

Generate tcc_union() accessors from header unions

Usage

```
tcc_treesitter_union_accessors(
  header,
  mapper = tcc_map_c_type_to_ffi,
  bitfield_type = "u8",
  include_bitfields = TRUE
)
```

Arguments

header	Character scalar containing C declarations.
mapper	Function to map C types to FFI types.
bitfield_type	FFI type to use for bitfields.
include_bitfields	Whether to include bitfields.

Value

Named list of accessors by union name. Bitfields are returned as lists with type, bitfield = TRUE, and width. Nested struct members are returned as list(type = "struct", struct_name = <name>) when the struct name is available, otherwise list(type = "struct").

Examples

```
## Not run:
header <- "union data { int i; double d; };"
tcc_treesitter_union_accessors(header)

## End(Not run)
```

tcc_treesitter_union_bindings

Apply tcc_union() bindings from a header

Description

Apply tcc_union() bindings from a header

Usage

```
tcc_treesitter_union_bindings(ffi, header, ...)
```

Arguments

ffi	A tcc_ffi object.
header	Character scalar containing C declarations.
...	Passed to tcc_treesitter_union_accessors().

Value

Updated tcc_ffi object.

Examples

```
## Not run:
header <- "union data { int i; double d; };"
ffi <- tcc_ffi()
ffi <- tcc_treesitter_union_bindings(ffi, header)

## End(Not run)
```

tcc_treesitter_union_members

Parse union members with treesitter.c

Description

Parse union members with treesitter.c

Usage

```
tcc_treesitter_union_members(header, ...)
```

Arguments

header	Character scalar containing C declarations.
...	Additional arguments passed to treesitter.c::get_union_members_from_root().

Value

A data frame of union members.

Examples

```
## Not run:
header <- "union data { int i; double d; };"
tcc_treesitter_union_members(header)

## End(Not run)
```

tcc_treesitter_unions *Parse union declarations with treesitter.c*

Description

Parse union declarations with treesitter.c

Usage

```
tcc_treesitter_unions(header, ...)
```

Arguments

header	Character scalar containing C declarations.
...	Additional arguments passed to <code>treesitter.c::get_union_nodes()</code> .

Value

A data frame of union nodes.

Examples

```
## Not run:
header <- "union data { int i; double d; };"
tcc_treesitter_unions(header)

## End(Not run)
```

tcc_union	<i>Declare union for FFI helper generation</i>
-----------	--

Description

Generate R-callable helpers for union allocation and member access. The union must be defined in a header.

Usage

```
tcc_union(ffi, name, members, active = NULL)
```

Arguments

ffi	A tcc_ffi object
name	Union name (as defined in C header)
members	Named list of union members with FFI types
active	Default active member for accessors

Value

Updated tcc_ffi object

Examples

```
## Not run:
ffi <- tcc_ffi() |>
  tcc_union("data_variant",
    members = list(as_int = "i32", as_float = "f32"),
    active = "as_int"
  )

## End(Not run)
```

tcc_write_bytes	<i>Write raw bytes to a pointer</i>
-----------------	-------------------------------------

Description

Write a raw vector into memory pointed to by an external pointer.

Usage

```
tcc_write_bytes(ptr, raw)
```

Arguments

ptr	External pointer
raw	Raw vector to write

Value

NULL.

tcc_write_f32	<i>Write a 32-bit float</i>
---------------	-----------------------------

Description

Write a 32-bit float

Usage

tcc_write_f32(ptr, offset, value)

Arguments

ptr	External pointer
offset	Byte offset
value	Integer value to write

Value

NULL (invisibly). Called for its side effect of writing one 32-bit floating-point value into native memory at ptr + offset.

tcc_write_f64	<i>Write a 64-bit double</i>
---------------	------------------------------

Description

Write a 64-bit double

Usage

tcc_write_f64(ptr, offset, value)

Arguments

ptr	External pointer
offset	Byte offset
value	Integer value to write

Value

NULL (invisibly). Called for its side effect of writing one 64-bit floating-point value into native memory at ptr + offset.

tcc_write_i16	<i>Write a signed 16-bit integer</i>
---------------	--------------------------------------

Description

Write a signed 16-bit integer

Usage

```
tcc_write_i16(ptr, offset, value)
```

Arguments

ptr	External pointer
offset	Byte offset
value	Integer value to write

Value

NULL (invisibly). Called for its side effect of writing one signed 16-bit value into native memory at ptr + offset.

tcc_write_i32	<i>Write a signed 32-bit integer</i>
---------------	--------------------------------------

Description

Write a signed 32-bit integer

Usage

```
tcc_write_i32(ptr, offset, value)
```

Arguments

ptr	External pointer
offset	Byte offset
value	Integer value to write

Value

NULL (invisibly). Called for its side effect of writing one signed 32-bit value into native memory at ptr + offset.

tcc_write_i64	<i>Write a signed 64-bit integer</i>
---------------	--------------------------------------

Description

Write a signed 64-bit integer

Usage

```
tcc_write_i64(ptr, offset, value)
```

Arguments

ptr	External pointer
offset	Byte offset
value	Integer value to write

Value

NULL (invisibly). Called for its side effect of writing one signed 64-bit value into native memory at ptr + offset.

tcc_write_i8	<i>Write a signed 8-bit integer</i>
--------------	-------------------------------------

Description

Write a signed 8-bit integer

Usage

```
tcc_write_i8(ptr, offset, value)
```

Arguments

ptr	External pointer
offset	Byte offset
value	Integer value to write

Value

NULL (invisibly).

tcc_write_ptr	<i>Write a pointer at byte offset</i>
---------------	---------------------------------------

Description

Write a pointer at byte offset

Usage

tcc_write_ptr(ptr, offset, value)

Arguments

ptr	External pointer (destination buffer)
offset	Byte offset
value	External pointer to write

Value

NULL (invisibly).

tcc_write_u16	<i>Write an unsigned 16-bit integer</i>
---------------	---

Description

Write an unsigned 16-bit integer

Usage

tcc_write_u16(ptr, offset, value)

Arguments

ptr	External pointer
offset	Byte offset
value	Integer value to write

Value

NULL (invisibly). Called for its side effect of writing one unsigned 16-bit value into native memory at ptr + offset.

tcc_write_u32	<i>Write an unsigned 32-bit integer</i>
---------------	---

Description

Write an unsigned 32-bit integer

Usage

```
tcc_write_u32(ptr, offset, value)
```

Arguments

ptr	External pointer
offset	Byte offset
value	Integer value to write

Value

NULL (invisibly). Called for its side effect of writing one unsigned 32-bit value into native memory at ptr + offset.

tcc_write_u64	<i>Write an unsigned 64-bit integer</i>
---------------	---

Description

Write an unsigned 64-bit integer

Usage

```
tcc_write_u64(ptr, offset, value)
```

Arguments

ptr	External pointer
offset	Byte offset
value	Integer value to write

Value

NULL (invisibly). Called for its side effect of writing one unsigned 64-bit value into native memory at ptr + offset.

tcc_write_u8	<i>Write an unsigned 8-bit integer</i>
--------------	--

Description

Write an unsigned 8-bit integer

Usage

```
tcc_write_u8(ptr, offset, value)
```

Arguments

ptr	External pointer
offset	Byte offset
value	Integer value to write

Value

NULL (invisibly). Called for its side effect of writing one unsigned 8-bit value into native memory at ptr + offset.

Index

`$.tcc_compiled`, 4

`as.character.tcc_cstring`, 5

`blas_lapack_info`, 5

`generate_trampoline`, 6

`get_external_ptr_addr`, 6

`is_callback_type`, 7

`parse_callback_type`, 7

`print.tcc_callback`, 8

`print.tcc_compiled`, 8

`print.tcc_cstring`, 9

`print.tcc_ffi`, 9

`tcc_add_file`, 10

`tcc_add_include_path`, 10

`tcc_add_library`, 11

`tcc_add_library_path`, 11

`tcc_add_symbol`, 12

`tcc_add_sysinclude_path`, 12

`tcc_bin_path(tcc_prefix)`, 35

`tcc_bind`, 13

`tcc_call_symbol`, 14

`tcc_callback`, 15

`tcc_callback_async_drain`, 16

`tcc_callback_async_schedule`, 16

`tcc_callback_close`, 17

`tcc_callback_ptr`, 17

`tcc_callback_valid`, 18

`tcc_cli(tcc_prefix)`, 35

`tcc_compile`, 18

`tcc_compile_string`, 19

`tcc_container_of`, 19

`tcc_cstring`, 20

`tcc_cstring()`, 23, 37

`tcc_cstring_object`, 20

`tcc_data_ptr`, 21

`tcc_data_ptr()`, 23

`tcc_enum`, 21

`tcc_ffi`, 22

`tcc_ffi()`, 14

`tcc_field_addr`, 22

`tcc_free`, 23

`tcc_free()`, 20, 21, 32

`tcc_generate_bindings`, 24

`tcc_get_symbol`, 25

`tcc_get_symbol()`, 31

`tcc_global`, 25

`tcc_header`, 26

`tcc_include`, 27

`tcc_include_path(tcc_prefix)`, 35

`tcc_include_paths`, 27

`tcc_introspect`, 28

`tcc_lib_path(tcc_prefix)`, 35

`tcc_lib_paths(tcc_prefix)`, 35

`tcc_library`, 28

`tcc_library_path`, 29

`tcc_link`, 29

`tcc_list_symbols`, 31

`tcc_malloc`, 31

`tcc_malloc()`, 23, 37

`tcc_map_c_type_to_ffi`, 32

`tcc_null_ptr`, 33

`tcc_options`, 33

`tcc_output`, 34

`tcc_path`, 34

`tcc_prefix`, 35

`tcc_ptr_addr`, 35

`tcc_ptr_free_set_null`, 36

`tcc_ptr_is_null`, 36

`tcc_ptr_is_owned`, 37

`tcc_ptr_set`, 37

`tcc_ptr_utils`, 38

`tcc_read_bytes`, 38

`tcc_read_cstring`, 39

`tcc_read_f32`, 39

`tcc_read_f64`, 40

tcc_read_i16, [40](#)
tcc_read_i32, [41](#)
tcc_read_i64, [41](#)
tcc_read_i8, [42](#)
tcc_read_ptr, [42](#)
tcc_read_u16, [43](#)
tcc_read_u32, [43](#)
tcc_read_u64, [44](#)
tcc_read_u8, [44](#)
tcc_recompile, [45](#)
tcc_relocate, [45](#)
tcc_relocate(), [31](#)
tcc_run_cli, [46](#)
tcc_set_options, [46](#)
tcc_source, [47](#)
tcc_state, [47](#)
tcc_struct, [48](#)
tcc_struct_raw_access, [48](#)
tcc_symbol_is_valid, [49](#)
tcc_sysinclude_paths
 (tcc_include_paths), [27](#)
tcc_treesitter_bindings, [49](#)
tcc_treesitter_defines, [50](#)
tcc_treesitter_enum_bindings, [51](#)
tcc_treesitter_enum_members, [52](#)
tcc_treesitter_enums, [52](#)
tcc_treesitter_functions, [53](#)
tcc_treesitter_global_types, [54](#)
tcc_treesitter_globals, [54](#)
tcc_treesitter_struct_accessors, [55](#)
tcc_treesitter_struct_bindings, [56](#)
tcc_treesitter_struct_members, [56](#)
tcc_treesitter_structs, [57](#)
tcc_treesitter_union_accessors, [58](#)
tcc_treesitter_union_bindings, [59](#)
tcc_treesitter_union_members, [59](#)
tcc_treesitter_unions, [60](#)
tcc_union, [61](#)
tcc_write_bytes, [61](#)
tcc_write_f32, [62](#)
tcc_write_f64, [62](#)
tcc_write_i16, [63](#)
tcc_write_i32, [63](#)
tcc_write_i64, [64](#)
tcc_write_i8, [64](#)
tcc_write_ptr, [65](#)
tcc_write_u16, [65](#)
tcc_write_u32, [66](#)
tcc_write_u64, [66](#)
tcc_write_u8, [67](#)